







对射式光电组件

封装形式	型号		接收器类型	槽宽 (mm)	接收端 孔径 (LxW)mm	接收器亮电流		上升和 下降时间 μs	内部收发 元件型号	工作温度 范围 °C
						最小值 (mA)	测试条件 @I _F (mA)			
 见 24 页	HOA0825-001 HOA0825-002 HOA0825-003 HOA0825-004		三极管	4.2	1.52 dia	0.5	20	15	SEP8506 SDP8406	-40 to 85
 见 24 页	HOA086... 或 HOA087...	0-L51 0-L55 1-L55 2-L55 5-L51 5-L55 6-L55 7-L55	三极管	3.2	1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27 1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27	0.50 0.50 1.00 1.80 0.50 0.50 1.00 1.80	20 20 10 20 20 20 10 20	15	SEP8506 SDP8406	-40 to 85
 见 24 页	HOA086... 或 HOA087...	0-N51 0-N55 1-N55 2-N55 5-N51 5-N55 6-N55 7-N55	三极管	3.2	1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27 1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27	0.50 0.50 1.00 1.80 0.50 0.50 1.00 1.80	20 20 10 20 20 20 10 20	15	SEP8506 SDP8406	-40 to 85
 见 24 页	HOA086... 或 HOA087...	0-P51 0-P55 1-P55 2-P55 5-P51 5-P55 6-P55 7-P55	三极管	3.2	1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27 1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27	0.50 0.50 1.00 1.80 0.50 0.50 1.00 1.80	20 20 10 20 20 20 10 20	15	SEP8506 SDP8406	-40 to 85
 见 24 页	HOA086... 或 HOA087...	0-T51 0-T55 1-T55 2-T55 5-T51 5-T55 6-T55 7-T55	三极管	3.2	1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27 1.52x0.25 1.57x1.27 1.57x1.27 1.57x1.27	0.50 0.50 1.00 1.80 0.50 0.50 1.00 1.80	20 20 10 20 20 20 10 20	15	SEP8506 SDP8406	-40 to 85
 见 24 页	HOA1872-001 HOA1872-002 HOA1872-003 HOA1872-011 HOA1872-012 HOA1872-013		三极管 三极管 达林顿 三极管 三极管 达林顿	2.5	1.27 dia	0.30 1.80 4.00 0.30	20	15 15 75 15	SE1450 SD1440 SD1410	-55 to 100
					1.52 dia	1.80 4.00		15 75	SEP8506 SDP8406 SDP8106	-40 to 85
 见 24 页	HOA1873-001 HOA1873-002 HOA1873-003 HOA1873-011 HOA1873-012 HOA1873-013		三极管 三极管 达林顿 三极管 三极管 达林顿	2.5	1.27 dia	0.30 1.80 4.00 0.30	20	15 15 75 15	SE1450 SD1440 SD1410	-55 to 100
					1.52 dia	1.80 4.00		15 75	SEP8506 SDP8406 SDP8106	-40 to 85
 见 24 页	HOA1874-001 HOA1874-002 HOA1874-003 HOA1874-011 HOA1874-012 HOA1874-013		三极管 三极管 达林顿 三极管 三极管 达林顿	3.1	1.27 dia	0.30 1.80 4.00 0.30	20	15 15 75 15	SE1450 SD1440 SD1410	-55 to 100
					1.52 dia	1.80 4.00		15 75	SEP8506 SDP8406 SDP8106	-40 to 85

对射式光电组件

封装形式	型号	接收器类型	槽宽 (mm)	接收端 孔径 (LxW)mm	接收器亮电流		上升和 下降时间 μs	内部收发 元件型号	工作温度 范围 °C
					最小值 (mA)	测试条件 @I _p (mA)			
 见 26 页	HOA1875-001 HOA1875-002 HOA1875-003	三极管 三极管 达林顿	5.1	1.27 dia	0.15 0.60 1.80	30	15 15 75	SE1450 SD1440 SD1410	-55 to 100
 见 27 页	HOA1876-001 HOA1876-002 HOA1876-003	三极管 三极管 达林顿	5.1	1.27 dia	0.15 0.60 1.80	30	15 15 75	SE1450 SD1440 SD1410	-55 to 100
 见 27 页	HOA1877-001 HOA1877-002 HOA1877-003	三极管 三极管 达林顿	9.5	1.27 dia	0.10 0.50 1.50	30	15 15 75	SE1450 SD1440 SD1410	-55 to 100
 见 27 页	HOA1879-011 HOA1879-012 HOA1879-013	三极管 三极管 三极管	3.2	1.52 dia 1.52 dia 1.02x0.25	0.40 1.80 0.50	20	15 15 15	SEP8506 SDP8406	-40 to 85
 见 27 页	HOA1882-011 HOA1882-012 HOA1882-013	三极管 三极管 达林顿	5.1	1.52 dia	0.30 1.80 4.00	20	15 15 75	SEP8506 SEP8706 SDP8406 SDP8106	-40 to 85
 见 27 页	HOA1883-011 HOA1883-012 HOA1883-013	三极管 三极管 达林顿	3.6	1.52 dia	0.30 1.80 4.00	20	15 15 75	SEP8506 SDP8406 SDP8106	-40 to 85
 见 27 页	HOA1884-011 HOA1884-012 HOA1884-013	三极管 三极管 达林顿	3.2	1.02x0.51	0.30 1.80 4.00	20	15 15 75	SEP8506 SDP8406 SDP8106	-40 to 85
 见 27 页	HOA1885-011 HOA1885-012 HOA1885-013	三极管 三极管 达林顿	5.1	1.52x1.27	0.30 1.80 4.00	20	15 15 75	SEP8506 SDP8406 SDP8106	-40 to 85
 见 27 页	HOA1886-011 HOA1886-012 HOA1886-013	三极管 三极管 达林顿	5.1	1.52x1.27	0.30 1.80 4.00	20	15 15 75	SEP8506 SEP8706 SDP8406 SDP8106	-40 to 85
 见 28 页	HOA1888-011 HOA1888-013	三极管 达林顿	12	1.52x1.52	0.50 2.00	20	15 75		-40 to 85
 见 28 页	HOA2862-001 HOA2862-002 HOA2862-003	三极管 三极管 达林顿	2.5	1.02x0.64	0.20 1.80 4.00	20	15 15 75	SE1450 SD1440 SD1410	-55 to 100
 见 28 页	HOA1889-011 HOA1889-013 (双通道)	三极管 达林顿	1.8	0.5	0.50 2.0	20	15 75	SEP8506 SDP8406 SDP8106	-40 to 85